


Bauarten / Design



Abmessungen Typ K 230 - 400
Dimensions Type K 230 - 400

Grösse Size	Übersetzung Ratio	D1	D2	D7	D8	D11	D12	D13	D21
230	1 - 2	32 _{j6}	32 _{j6}	M10	11	95 _{f7}	135 _{f7}	115	95 _{f7}
	3 + 4	28 _{j6}							
	5 + 6	24 _{j6}							
250	1 - 2	35 _{j6}	35 _{j6}	M12	13,5	110 _{f7}	156 _{f7}	135	110 _{f7}
	3 + 4	28 _{j6}							
	5 + 6	24 _{j6}							
300	1 - 2	42 _{j6}	42 _{j6}	M12	13,5	120 _{f7}	198 _{f7}	175	120 _{f7}
	3 + 4	35 _{j6}							
	5 + 6	28 _{j6}							
370	1 - 2	55 _{j6}	55 _{j6}	M16	17,5	150 _{f7}	225 _{f7}	200	150 _{f7}
	3 + 4	40 _{j6}				140 _{f7}			
	5 + 6	35 _{j6}							
400	1 - 2	60 _{j6}	60 _{j6}	M16	17,5	160 _{f7}	258 _{f7}	230	160 _{f7}
	3 + 4	50 _{j6}							
	5 + 6	45 _{j6}							

Grösse Size	Übersetzung Ratio	L1	L2	L7	L10	L12	L14	L20	L22	L24	L71	R	Passfeder D1 Keyway D1	Passfeder D2+D3 Keyway D2+D3
230	1 - 2	50	50	140	180	85	2	180	85	2	110	2	10 x 8 x 45	10 x 8 x 45
	3 + 4				195								8 x 7 x 40	
	5 + 6				195								8 x 7 x 40	
250	1 - 2	60	60	160	212	95	2	212	95	2	120	2	10 x 8 x 45	10 x 8 x 45
	3 + 4				227								8 x 7 x 45	
	5 + 6				222								8 x 7 x 40	
300	1 - 2	80	80	200	273	120	3	273	120	3	160	3	12 x 8 x 60	12 x 8 x 60
	3 + 4				261		2						10 x 8 x 45	
	5 + 6				248								8 x 7 x 45	
370	1 - 2	90	90	230	305	135	2	305	135	2	180	5	16 x 10 x 80	16 x 10 x 80
	3 + 4				310								12 x 8 x 60	
	5 + 6				300								10 x 8 x 50	
400	1 - 2	110	110	260	380	150	5	380	150	5	220	5	18 x 11 x 90	18 x 11 x 90
	3 + 4	90			360								14 x 9 x 70	
	5 + 6				360								14 x 9 x 70	