



Standard Indexer						
Number of stops n	Index angle $\alpha$ [°] from - to	Law of motion	Output torque at indexes/min [Nm]			Followers at pitch radius [mm]
			50	100	200	
1	300	mS 50	766	612	455	62
	330	mS 30	770	618	474	62
2	165	mS 50	893	708	506	62
	180-210	mS 30	859	689	526	62
	240-300	mS 0	812	656	518	62
3	135-150	mS 30	1059	942	720	62
	180-210	mS 0	1065	892	705	62
	240-300	mS 0	997	807	646	62
4	105	mS 30	887	870	688	62
	120-180	mS 0	873	841	663	62
	210-300	mS 0	840	726	583	62
5	120-180	mS 0	969	965	835	74
	210-300	mS 0	927	902	726	74
6*	180-210	mS 0	1045	1043	869	62
	240-300	mS 0	1017	973	786	62
8*	150-210	mS 0	840	838	779	62
	240-300	mS 0	817	816	703	62

- Standard followers -  $\varnothing$  52 mm.
- Housing made of cast iron, weight approx. 120 kg.
- Internal moment of inertia 0,07 kgm<sup>2</sup>.
- Torque during dwell approx. 20 % higher than permissible torque at 50 indexes/min.
- Keyways on input and output shafts positioned in the middle of a dwell.
- Keyways to DIN 6885/1.
- Reversibility of rotation possible.
- Long life lubrication.
- \* Indexer with 6 or 8 stops requires 2 revolutions per input shaft rotation.
- Drawings with detailed dimensions available on CAD (DXF, DWG).
- A full range of reducer, clutch and brake options, as well as output overloads, is available.
- A wide range of further number of stops, index angles, and motion laws including oscillating movements is available.
- All rights reserved for technical changes.