



Standard Indexer						
Number of stops n	Index angle α [°] from - to	Law of motion	Output torque at indexes/min [Nm]			Followers at pitch radius [mm]
			50	100	200	
1	300	mS 50	2237	1745	1129	96
	330	mS 50	2172	1704	1146	96
2	165	mS 50	2616	2005	1151	96
	180-210	mS 30	2524	1991	1381	96
	240-300	mS 0	2387	1914	1455	96
3	135-150	mS 30	3383	2711	1893	96
	180-210	mS 0	3236	2595	1972	96
	240-300	mS 0	2922	2357	1848	96
4	105	mS 30	2834	2662	1689	96
	120-180	mS 0	2802	2453	1854	96
	210-300	mS 0	2638	2130	1680	96
5	120-180	mS 0	3002	2960	2281	112
	210-300	mS 0	2873	2549	2026	112
6*	180-210	mS 0	3349	3164	2502	96
	240-300	mS 0	3257	2852	2283	96
8*	150-210	mS 0	2698	2686	2259	96
	240-300	mS 0	2791	2785	2460	96

- Standard followers - \varnothing 80 mm.
- Housing made of cast iron, weight approx. 320 kg.
- Internal moment of inertia 0,5 kgm².
- Torque during dwell approx. 20 % higher than permissible torque at 50 indexes/min.
- Keyways on input and output shafts positioned in the middle of a dwell.
- Keyways to DIN 6885/1.
- Reversibility of rotation possible.
- Long life lubrication.
- * Indexer with 6 or 8 stops requires 2 revolutions per input shaft rotation.
- Drawings with detailed dimensions available on CAD (DXF, DWG).
- A full range of reducer, clutch and brake options, as well as output overloads, is available.
- A wide range of further number of stops, index angles, and motion laws including oscillating movements is available.
- All rights reserved for technical changes.